400 Seventh St., S.W. Washington, D.C. 20590

AUG 1 3 2001

DOT-E 12124 (FIFTH REVISION)

EXPIRATION DATE: September 30, 2002

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Albemarle Corporation Baton Rouge, LA

PURPOSE AND LIMITATION: 2.

- This exemption authorizes the transportation in а. commerce of certain Division 4.2 and Division 4.3 materials in a non-DOT specification portable tank comparable to a specification DOT 51 portable tank. This exemption provides no relief from any Hazardous Materials Regulation (HMR) other than as specifically stated herein.
- b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
- REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-3. 180.
- REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.242 in that a 4. non-DOT specification portable tank is not authorized, except as specified herein.
- 5. BASIS: This exemption is based on the application of Albemarle Corporation dated September 15, 2000, submitted in accordance with § 107.109, and additional letters dated January 25, 2001 and July 24, 2001 SAMBLE PARTY

A Maria

in granded to the College of Asia

Cylina.

. derger -

and the second

ich ir

, 6.

1000 m 1000 m 1000 m

55.15

6. <u>HAZARDOUS MATERIALS (49 CFR § 172.101)</u>:

AUG 1 3 7001

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Organometallic compound, water- reactive, flammable, n.o.s.	4.3	UN3207	I
Pyrophoric organometallic compound, solid, water-reactive, n.o.s.	4.2	UN3203	I
Pyrophoric solid, inorganic, n.o.s.	4.2	UN3200	I
Water-reactive solid, corrosive, n.o.s.	4.3	UN3131	I
Water-reactive solid, n.o.s.	4.3	UN2813	I

7. <u>SAFETY CONTROL MEASURES</u>:

- a. <u>PACKAGING</u> Packaging is a non-DOT specification stainless steel portable tank conforming to the configuration and dimensions shown in Albemarle Drawing number D-ALB.PROD.CON, Rev 0 dated October 20, 1998 on file with the Office of Hazardous Materials Exemptions and Approvals. The portable tank has the following features:
 - (1) a minimum wall thickness of 9.5 mm (0.375 in);
 - (2) a maximum allowable working pressure of 8.62 bar
 (125 psig);
 - (3) a capacity not to exceed 880 liters (232 gallons);
 - (4) a cone-shaped funnel bottom with an eductor and block valves;
 - (5) a maximum loading or discharge pressure of 3.5 bar (50 psig); and
 - (6) a spring loaded pressure relief valve set at 8.62 bar (125 psig).

in property deligibles and the second

A TOP IN

The Cappellant of the Cappella

The second of th

4.50 6.50

align.

In addition, the portable tank must conform with specification DOT 51 (§ 178.245), including ASME certification and "U" stamp, except as follows:

AUG 1 3 2001

- (1) § 178.245-1(c). The tank has a bottom discharge fitted with an eductor and block valves in addition to openings on the top of the tank.
- (2) § 178.245-1(d)(4). The portable tank is not mounted in a full framework for containerized transport and the bottom discharge is not fitted with an internal self-closing stop-valve.
- (3) § 178.245-7(a). The line on the name plate which reads "DOT Specification No." must be marked "DOT-E 12124".
- b. <u>TESTING</u> Each portable tank must be tested and periodically requalified as required for a DOT Specification 51 steel portable tank. Minimum test pressure is 12.93 bar (187.5 psig).

c. OPERATIONAL CONTROLS -

- (1) Bottom outlets must be closed with two devices during transportation. A discharge valve provides the first device. The secondary device may be a blind flange, a threaded plug or a camlock cap.
- (2) A dry nitrogen blanket of 0.7 bar (10 psig) must be applied to the lading during transportation.

8. SPECIAL PROVISIONS:

- a. A person who is not a holder of this exemption who receives a package covered by this exemption may reoffer it for transportation provided no modifications or changes are made to the package and it is reoffered for transportation in conformance with this exemption and the HMR.
- b. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.
- c. This exemption serves as a Competent Authority Approval (CA-9812012), issued by the Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration of the United States Department of

J. France (1989) 13.55 ir Tu

· 新國和高級。25.

激化的结合 1500

Transportation, in accordance with Section 22 of the International Maritime Dangerous Goods (IMDG) Code.

- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle and cargo vessel.
- MODAL REQUIREMENTS: A current copy of this exemption must 10. be carried aboard each cargo vessel or motor vehicle used to transport packages covered by this exemption.
- COMPLIANCE: Failure by a person to comply with any of the 11. following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
 - All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - Registration required by § 107.601 et seq., when \circ applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incldent involving the package and made under the terms of this exemption. writing, of any incident involving the package and shipments

- See Prince by

ા વૈદ્ધાલ A 4 2

A Company of the comp

align the said 1 2 43 13137 Issued in Washington, D.C.:

To Robert A. McGuire

Assoc \mathcal{A} te Administrator for Hazardous Materials Safety AUG 1 3 2001

(DATE)

William Sp.

THE PERSON OF TH

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590. Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, S.W., Washington, DC 20590-0001, Attention: Records Center, 202-366-5046.

> the transition of nga gargaratana s **** *****

g Barry S

Parang American

antigen of applied તેપુર્લેશાન જ કુલાય 19.00

entre ha se prome men de la companya-men de la companya-de la company

PO: AM